

Datum: 16.12.2025



(slika je simbolična)

2/2-el.mag.vent.,NC,prisil.vod. krm.,230-240V,G3/4,0-14bar

Kategorija: [Solenoid valve, NC, combined operation](#)

Šifra: **102906RIE**

Kratek opis

2/2-way solenoid valve brass,NC,force pilot operated,230-240V,50-60Hz,16VA, Medium temp. -10°C to 90°C, NBR+PA, G 3/4, PN 0-14bar

Economy series available in three different versions

- Directly operated
- Combined operation
- Pilot-operated

For all applications with compressed air, neutral gases or low-viscosity, neutral media.

Tehnične Specifikacije

Min. sobna temperatura [°C]	-10
Min. temperatura medija [°C]	-10
Električni priključek	For connector socket Pg 9/Pg 11 acc. to ISO 4400
Ffunkcija	normally closed (NC)
IP zaščita	IP 65 (with connector socket fitted)
Navoj	G 3/4
Notranji deli	Stainless steel
Ohišje	Brass
Sedež ventila	Brass
Tesnilo	NBR
Vrsta	8
Max. obratovalni tlak [bar]	14
DN	16
A [mm]	54.0
B [mm]	70.0
Max. sobna temperatura [°C]	80
Max. temperatura medija [°C]	90