

Datum: 29.04.2025



2/2-el.mag.vent.,NO,direkt. krm., 24V DC,8W, G1/8,0-20bar

(slika je simbolična)

Kategorija: [Solenoid valve, NO, directly operated](#)

Šifra: **102900RIE**

Kratek opis

2/2-way solenoid valve brass, NO, directly operated, 24V DC, 8W, Medium temp. -10°C to 140°C, FKM, G 1/8, PN 0 - 20bar

Economy series available in three different versions

- Directly operated
- Combined operation
- Pilot-operated

For all applications with compressed air, neutral gases or low-viscosity, neutral media.

Tehnične Specifikacije

Min. sobna temperatura [°C]	-10
Min. temperatura medija [°C]	-10
Električni priključek	For connector socket Pg 9/Pg 11 acc. to ISO 4400
Ffunkcija	normally open (NO)
IP zaščita	IP 65 (with connector socket fitted)
Navoj	G 1/8
Notranji deli	Stainless steel
Ohišje	Brass
Sedež ventila	Brass
Tesnilo	FPM
DN	2
Vrsta	2
Max. obratovalni tlak [bar]	20
B [mm]	40.0
A [mm]	54.0
Max. sobna temperatura [°C]	80
Max. temperatura medija [°C]	140