

Datum: 16.12.2025



2/2-el.magn.ventil,NC,direkt.krm.,230V,50Hz,FPM,G1/8,PN0-6bar

(slika je
simbolična)

Kategorija: [Solenoid valve, NC, directly operated](#)
Šifra: **102884RIE**

Kratek opis

2/2-way solenoid valve brass, NC, directly operated, 230V, 50Hz, 5VA, Medium temp. -10°C to 140°C, FPM, G 1/8, PN 0 - 6bar

Economy series available in three different versions

- Directly operated
- Combined operation
- Pilot-operated

For all applications with compressed air, neutral gases or low-viscosity, neutral media.

Tehnične Specifikacije

Min. sobna temperatura [°C]	-10
Min. temperatura medija [°C]	-10
Električni priključek	For connector socket Pg 9/Pg 11 acc. to ISO 4400
Ffunkcija	normally closed (NC)
IP zaščita	IP 65 (with connector socket fitted)
Navoj	G 1/8
Notranji deli	Stainless steel
Ohišje	Brass
Sedež ventila	Brass
Tesnilo	FPM
Vrsta	1
DN	2.3
Max. obratovalni tlak [bar]	6
B [mm]	30.0
A [mm]	41.0
Max. sobna temperatura [°C]	60
Max. temperatura medija [°C]	140