

Datum: 30.04.2025



(slika je simbolična)

2/2-potni el.mag. ventil, NC, direk. upr., 24 V DC, G 1/4

Kategorija: [Solenoid valve, NC, directly operated](#)

Šifra: **102826RIE**

Kratek opis

2/2-way solenoid valve, brass, NC, direc. operat., 24V DC, Med. temp. -15 to 120°C, Ambient temp. -15 to 55°C, FPM, G 1/4, PN 0-8bar

Standard series, proven over many years, available in three different versions

- Directly operated
- Combined operation
- Pilot-operated

For all applications with compressed air, neutral gases or low-viscosity, neutral media.

Tehnične Specifikacije

Min. sobna temperatura [°C]	-15
Min. temperatura medija [°C]	-15
Električni priključek	ISO 4400, cable socket (Pg 11P)
Ffunkcija	normally closed (NC)
IP zaščita	IP65 (with connector socket fitted)
Navoj	G 1/4
Notranji deli	Stainless steel
Ohišje	Brass
Sedež ventila	Brass
Standardni navoj	G thread acc. to DIN EN ISO 228-1
Tesnilo	FPM
Vrsta	2
DN	3.2
Max. obratovalni tlak [bar]	8
B [mm]	30.0
Max. sobna temperatura [°C]	55
A [mm]	91.0
Max. temperatura medija [°C]	120