

Datum: 29.04.2025



(slika je simbolična)

## 2/2-potni el.mag. ventil, NO, direk. upr., 24 V DC, G 1/4

Kategorija: [Solenoid valve, NO, directly operated](#)

Šifra: **102832RIE**

### Kratek opis

2/2-way solenoid valve, brass, NO, direc. operat., 24V DC, Med. temp. -25 to 80°C, Ambient temp. -25 to 55°C, NBR, G 1/4, PN 0-6.5bar

Standard series, proven over many years, available in three different versions

- Directly operated
- Combined operation
- Pilot-operated

For all applications with compressed air, neutral gases or low-viscosity, neutral media.

### Tehnične Specifikacije

|                              |                                     |
|------------------------------|-------------------------------------|
| Min. sobna temperatura [°C]  | -25                                 |
| Min. temperatura medija [°C] | -25                                 |
| Električni priključek        | ISO 4400, cable socket (Pg 11P)     |
| Ffunkcija                    | normally open (NO)                  |
| IP zaščita                   | IP65 (with connector socket fitted) |
| Navoj                        | G 1/4                               |
| Notranji deli                | Stainless steel                     |
| Ohišje                       | Brass                               |
| Sedež ventila                | Brass                               |
| Standardni navoj             | G thread acc. to DIN EN ISO 228-1   |
| Tesnilo                      | NBR                                 |
| Vrsta                        | 2                                   |
| DN                           | 3.2                                 |
| Max. obratovalni tlak [bar]  | 6.5                                 |
| B [mm]                       | 40.0                                |
| Max. sobna temperatura [°C]  | 55                                  |
| A [mm]                       | 80.0                                |
| Max. temperatura medija [°C] | 80                                  |