

Datum: 15.12.2025



## 3-potni krogelni ventil, nikljana medenina, T-izpust, Rp 1/4

(slika je simbolična)

Kategorija: [3-way ball valve, lower media connection, T-bore](#)

Šifra: **136334RIE**

### Kratek opis

3-way ball valve, nickel-plated brass, Connection bottom, T-hole, Rp 1/4, DN 8, Operating temp. -15 °C to 120 °C, PN max. 25 bar

3-way ball valve with full throughput, integrated ISO flange plate (ISO 5211) and double-sided sealed ball.

Pressurisation is only possible via the lower connection.

### Tehnične Specifikacije

|                               |                              |
|-------------------------------|------------------------------|
| Min. delovna temperatura [°C] | -15                          |
| Krogelno tesnilo              | PTFE                         |
| Krogla                        | Nickel-plated brass (CW617N) |
| Material navojev              | Brass                        |
| Navoj                         | Rp 1/4                       |
| Ohišje                        | Nickel-plated brass (CW617N) |
| Ročica                        | Steel with plastic coating   |
| Standardni navoj              | Rp thread acc. to ISO 7-1    |
| Stebelno tesnilo              | PTFE / FKM                   |
| DN                            | 8                            |
| E [mm]                        | 11.0                         |
| a/f [mm]                      | 22                           |
| PN [bar]                      | 25                           |
| H2 [mm]                       | 26.0                         |
| H1 [mm]                       | 28.5                         |
| L [mm]                        | 52.0                         |
| B [mm]                        | 60.0                         |
| A [mm]                        | 115.0                        |
| Max. delovna temperatura [°C] | 120                          |