

Datum: 29.04.2025



(slika je simbolična)

3-potni krogelni ventil, nikljana medenina, T-izpust, Rp 1

Kategorija: [3-way ball valve, lower media connection, T-bore](#)

Šifra: **136338RIE**

Kratek opis

3-way ball valve, nickel-plated brass, Connection bottom, T-hole, Rp 1, DN 25, Operating temp. -15°C to 120°C, PN max. 16 bar

3-way ball valve with full throughput, integrated ISO flange plate (ISO 5211) and double-sided sealed ball. Pressurisation is only possible via the lower connection.

Tehnične Specifikacije

Min. delovna temperatura [°C]	-15
Krogelno tesnilo	PTFE
Krogla	Nickel-plated brass (CW617N)
Material navojev	Brass
Navoj	Rp 1
Ohišje	Nickel-plated brass (CW617N)
Ročica	Steel with plastic coating
Standardni navoj	Rp thread acc. to ISO 7-1
Stebelno tesnilo	PTFE / FKM
PN [bar]	16
E [mm]	19.1
DN	25
a/f [mm]	41
H1 [mm]	45.0
H2 [mm]	47.0
B [mm]	76.0
L [mm]	89.0
A [mm]	115.0
Max. delovna temperatura [°C]	120