

Datum: 15.12.2025



(slika je simbolična)

## 3-potni medenina krogelni ventil, Pneumat. vklop, L-izpust, Rp 2

Kategorija: [Brass ball valve, double-acting actuator, L-bore](#)

Šifra: **103554RIE**

### Kratek opis

3-way brass ball valve, Pneumat. actuation drive, L-hole,  
Operating temperature -20 °C to 70 °C, Rp 2, DN 50, PN  
max. 25 bar  
3-way cock, L-bore or T-bore, full bore.  
Pneumatic actuators, double- or single acting version and  
integrated end-position feedback.

### Tehnične Specifikacije

|                                   |                                            |
|-----------------------------------|--------------------------------------------|
| Min. delovna temperatura [°C]     | -20                                        |
| Adapter ventila                   | Supplied as standard                       |
| Material krogelnega ventila       | Nickel-plated brass, with ISO flange plate |
| Navoj                             | Rp 2                                       |
| Pogonski material                 | Anodised aluminium                         |
| Položaj                           | L 2                                        |
| Premaz za krogelni ventil         | PTFE / FKM                                 |
| Premaz za pogon                   | NBR                                        |
| Različica                         | double-acting                              |
| Priporočeni vodeni tlak [bar]     | 5.5                                        |
| Max. vodeni tlak aktuatorja [bar] | 10                                         |
| PN [bar]                          | 25                                         |
| DN                                | 50                                         |
| D [mm]                            | 56.0                                       |
| a/f [mm]                          | 67                                         |
| Max. delovna temperatura [°C]     | 70                                         |
| Kot vrtenja [°]                   | 90                                         |
| L [mm]                            | 157.0                                      |
| A [mm]                            | 161.0                                      |
| B [mm]                            | 204.0                                      |