

Datum: 16.12.2025



(slika je simbolična)

## 3/2-5/2-potni ventil NAMUR, G 1/4 (1), G 1/4 (3+5), 230 V, 50 Hz

Kategorija: [3/2 and 5/2-way valves NAMUR](#)

Šifra: **103649RIE**

### Kratek opis

3/2-5/2-way valve NAMUR, Alu, Temp. -5 °C to 50 °C, Working pressure 1.5-8 bar, Connection G 1/4 (1), G 1/4 (3 + 5), 230 V, 50 Hz  
Pilot-operated 3/2 and 5/2-way spool valves with threaded ports and a NAMUR style interface.  
Combines high-quality design with a low price.  
By adding the conversion plate supplied with each valve, the device can be adapted to a 3/2-way function.  
The valve is turned on by a continuous signal. Turning off causes the piston to be returned to its initial position under pressure.  
Includes a manual operator as standard.

### Tehnične Specifikacije

|                               |                                        |
|-------------------------------|----------------------------------------|
| Min. delovna temperatura [°C] | -5                                     |
| Električni priključek         | Connector socket PG 9 with LED display |
| Ohišje                        | Aluminium                              |
| Port 1                        | G 1/4                                  |
| Port 3                        | G 1/4                                  |
| Port 5                        | G 1/4                                  |
| Ročno upravljanje             | latching/non-latching                  |
| Srednje                       | Air, neutral gases (filtered)          |
| Tesnilo                       | NBR                                    |
| Min. delovni tlak [bar]       | 1.5                                    |
| DN                            | 8                                      |
| Max. delovni tlak [bar]       | 8                                      |
| Max. delovna temperatura [°C] | 50                                     |
| Napetost                      | 230 V, 50 Hz                           |
| Pretok [l/min]                | 1370                                   |