

Datum: 01.05.2025



(slika je simbolična)

3/2 blokirni ventil »G«, Velikost 400, G 1/2

Kategorija: [3/2-way shut-off valves](#)

Šifra: **116437RIE**

Kratek opis

3/2-way blocking valve »G«, Mounting bracket, Padlock and silencer, Manually actuated, Size 400, G 1/2, Input pressure 0 - 9 bar

Rotary switch can be turned 90°, lockable.

The valve is used to switch off the air supply and is normally installed upstream of a pressure regulator, filter regulator or service unit.

When the valve is closed, the residual air on the P2 side is discharged into the atmosphere through the relief port on the bottom.

Tehnične Specifikacije

Merjenje pretoka	At $P_1 = 8$ bar, $P_2 = 6$ bar and pressure drop $\Delta p = 1$ bar
Navoj	G 1/2
Odzračevalni vtič	G 1/2
Ohišje	Die-cast aluminium
Serijska	G
Tesnilo	NBR
Zasučni gumb	Plastics
Max. vhodni tlak [bar]	9
D [mm]	58.5
A [mm]	63.0
Max. sobna temperatura [°C]	70
Max. temperatura medija [°C]	70
C [mm]	75.5
B [mm]	134.0
Velikost	400
Pretok [l/min]	6200