

Datum: 30.04.2025



(slika je simbolična)

3/2-potni el.mag. ventil med., NC, 24 V DC, FKM, G 1/8

Kategorija: [Solenoid valves 3/2-way type, NC, brass](#)

Šifra: **102962RIE**

Kratek opis

3/2-way solenoid valve brass, NC, 24 V DC, Sealing material FKM, Medium temperature -10 °C to 100 °C, G 1/8, PN 0 - 15 bar

Directly operated seat valve with spring return and manual operator.

Also suitable for vacuum operation.

Tehnične Specifikacije

Min. sobna temperatura [°C]	-10
Min. temperatura medija [°C]	-10
Aplikacije	Compressed air and neutral, non-toxic gases, water, oil
Električni priključek	Connector socket, can be rotated 180°, PG7 acc. to 43650
Ffunkcija	interchangeable magnetic heads (AC/DC)
IP zaščita	IP 65 (with connector socket fitted)
Navoj	G 1/8
Notranji deli	Stainless steel
Ohišje	Brass
Tesnilo	FPM
DN	1.2
Max. obratovalni tlak [bar]	15
Napetost	24 V DC
B [mm]	33.0
A [mm]	58.0
Max. sobna temperatura [°C]	60
Max. temperatura medija [°C]	100