

Datum: 16.12.2025



(slika je simbolična)

## 3/2-potni magnetni ventil »lineonline« z dušilko, za cev Ø8, NO

Kategorija: [3/2-way Solenoid valve, exhaust damped by silencer](#)

Šifra: **106846RIE**

### Kratek opis

3/2-way solenoid valve »lineonline« silenced venting, Hose - hose, Hose Ø 8, NO, 24 V DC, Operating pressure 2.5 - 7 bar  
Though small in size, these valves are solenoid-piloted and feature very high performance.

Each valve comes complete with a monostable manual control and LED. Exhaust can be damped with a silencer or conveyed via a pipe fitting.

Function corresponds to the normal position of the valve.

### Tehnične Specifikacije

|                                          |                                                            |
|------------------------------------------|------------------------------------------------------------|
| Min. temperaturno območje [°C]           | -20                                                        |
| Ffunkcija                                | NO                                                         |
| Notranji deli                            | Nickel-plated brass, brass, technopolymer, stainless steel |
| Pnevmatski simboli                       | On housing                                                 |
| Telo                                     | Technopolymer                                              |
| Tesnilo                                  | NBR                                                        |
| Vhodna moč                               | 1.2 W                                                      |
| Min. obratovalni tlak [bar]              | 2.5                                                        |
| Max. obratovalni tlak [bar]              | 7                                                          |
| Za cevi Ø [mm]                           | 8                                                          |
| l [mm]                                   | 18.7                                                       |
| Operativna napetost                      | 24 V DC                                                    |
| A [mm]                                   | 57.2                                                       |
| Max. temperaturno območje [°C]           | 60                                                         |
| B [mm]                                   | 63.5                                                       |
| Pretok pri 6,3 bar in Δp 1,0 bar [l/min] | 700                                                        |