

Datum: 15.12.2025



(slika je simbolična)

## 5/2-pot.vent., enostranski el.magnet., monostab. G1/2 24VDC

Kategorija: [5/2-way spool valve, single solenoid](#)

Šifra: **106593RIE**

### Kratek opis

5/2-way valve, Single-sided electromagnetic, monostable, G 1/2, 24 V DC, Operating pre. 2.5-10 bar, Operating temp. -10°C to 60°C

This valve design, featuring the Tapered Tee Seal®, offers the ability to run without lubrication and supports almost any compressed air quality.

The valves are largely resistant to dirt and can thus also be used under extreme conditions without any problems.

Leakage is now a thing of the past and the spool no longer sticks, even after long idle periods.

### Tehnične Specifikacije

|                                |                                   |
|--------------------------------|-----------------------------------|
| Min. temperaturno območje [°C] | -10                               |
| Delovanje                      | Monostable                        |
| Električni priključek          | Coupler plug PG 9, form B         |
| IP zaščita                     | IP 65 (DIN 46244)                 |
| Merjenje pretoka 1             | Flow rate at 6 bar and ?p 1.0 bar |
| Ohišje                         | Anodised aluminium, blue          |
| Povezava                       | G 1/2                             |
| Ročno upravljanje              | non-latching                      |
| Tesnilo                        | NBR                               |
| Tuljava                        | Stainless steel                   |
| Min. obratovalni tlak [bar]    | 2.5                               |
| Min. vodeni tlak [bar]         | 2.5                               |
| Ffunkcija                      | 5/2                               |
| Max. obratovalni tlak [bar]    | 10                                |
| DN                             | 15                                |
| Napetost                       | 24 V DC                           |
| Simbol                         | 35                                |
| Max. temperaturno območje [°C] | 60                                |
| Pretok 1 [NI/min]              | 4600                              |