

Datum: 29.04.2025



(slika je simbolična)

Active charcoal filter without differential pressure gauge, G 3/8

Kategorija: [Activated carbon filter without differential pressure gauge](#)
Šifra: **199818RIE**

Kratek opis

Active charcoal filter without differential pressure gauge,
0.003 mg/m³, G 3/8, Input pressure 4 - 16 bar, Temp. 1.5 °C
to 80 °C

For adsorbing vaporous media.

A micro-filter must be connected upstream if dried air is not
available.

Tehnične Specifikacije

Element filtra	non-woven medium, impregnated with activated carbon
Merjenje pretoka	At P ₁ = 7 bar and pressure drop Δ _p = 0.1 bar
Navoj	G 3/8
Ohišje	Aluminium
Posoda filtra	Aluminium
Rang filtra [μm]	0.00
Vsebnost olja v ostanku [mg/m ³]	0.003
Min. sobna temperatura [°C]	1.5
Min. temperatura medija [°C]	1.5
Max. vhodni tlak [bar]	16
C [mm]	23.5
A [mm]	80.0
Max. sobna temperatura [°C]	80
Max. temperatura medija [°C]	80
Učinkovitost [%]	99.9999
D [mm]	327.0
Pretok [l/min]	1000