

Datum: 30.04.2025



(slika je simbolična)

## Batni kotni ventil, NC, bronasti, G 2

Kategorija: [Angle-seat valves, piston actuator bronze version](#)Šifra: **133205RIE**

### Kratek opis

Angle seat valve, Piston drive without NAMUR interface, Bronze, Medium temp. -10°C to 180°C, G 2, Pressure difference max 10 bar

Angle-seat valves with external pilot control and a self-aligning valve disc for neutral (bronze body) or corrosive (stainless steel body) media.

- Very high flow due to angled seat design
- Water hammer prevented by fluid entry under the disc
- Suitable for vacuum operation (low vacuum)

### Tehnične Specifikacije

|                                       |                                    |
|---------------------------------------|------------------------------------|
| Min. sobna temperatura [°C]           | -20                                |
| Min. temperatura medija [°C]          | -10                                |
| Bat                                   | PBT + GF 30 %                      |
| Ffunkcija                             | NC                                 |
| Nadzor zraka                          | G 1/8                              |
| Navoj                                 | G 2                                |
| Ohišje                                | Bronze                             |
| Operater                              | Polyamide (glass fibre-reinforced) |
| Priključki                            | Stainless steel                    |
| Steblo                                | Stainless steel                    |
| Tesnilo                               | PTFE                               |
| Min. vodeni tlak [bar]                | 4                                  |
| Max. vodeni tlak [bar]                | 8                                  |
| Max. razlika v delovnem tlaku [bar]   | 10                                 |
| Diferencialni tlak max. [bar]         | 16                                 |
| Max. dovoljeni statični tlak [bar]    | 16                                 |
| Max. temperatura vodenega medija [°C] | 60                                 |
| Max. sobna temperatura [°C]           | 70                                 |
| F [mm]                                | 150.0                              |
| Max. temperatura medija [°C]          | 180                                |
| C [mm]                                | 311.0                              |
| A [mm]                                | 316.0                              |