

Datum: 30.04.2025



(slika je simbolična)

Batni kotni ventil, NC, nerjavno jeklo, G 1/2

Kategorija: [Angle-seat valves, piston actuator stainless steel](#)

Šifra: **133206RIE**

Kratek opis

Angle seat valve, Piston drive without NAMUR interface, NC, Medium temp. -10°C to 180°C, G 1/2, Pressure difference max 16 bar

Angle-seat valves with external pilot control and a self-aligning valve disc for neutral (bronze body) or corrosive (stainless steel body) media.

- Very high flow due to angled seat design
- Water hammer prevented by fluid entry under the disc
- Suitable for vacuum operation (low vacuum)

Tehnične Specifikacije

Min. sobna temperatura [°C]	-20
Min. temperatura medija [°C]	-10
Bat	Nickel-plated brass
Ffunkcija	NC
Nadzor zraka	G 1/8
Navoj	G 1/2
Ohišje	Stainless steel AISI 316
Operater	Polyamide (glass fibre-reinforced)
Priključki	Stainless steel
Steblo	Stainless steel
Tesnilo	PTFE
Min. vodeni tlak [bar]	4
Max. vodeni tlak [bar]	10
Diferencialni tlak max. [bar]	16
Max. dovoljeni statični tlak [bar]	16
Max. razlika v delovnem tlaku [bar]	16
Max. temperatura vodenega medija [°C]	60
Max. sobna temperatura [°C]	70
F [mm]	85.0
C [mm]	169.0
Max. temperatura medija [°C]	180
A [mm]	190.0