

Datum: 16.12.2025



(slika je simbolična)

## **Bimetalni termometer, zadaj, L1=100 mm / L2=80 mm, Ø 100**

Kategorija: [Bimetallic thermometers \(high-quality type\)](#)

Šifra: **102801RIE**

### **Kratek opis**

Bi-metallic thermometer, High quality design, Connection rear, for protective pipe L1=100 mm/L2=80 mm, Display range 0°C to 120°C

Applications: Extremely versatile design for use in machine, vessel, pipeline and plant construction as well as for heating systems.

A thermowell (removable with locking screw) is required.

### **Tehnične Specifikacije**

|                                            |                                            |
|--------------------------------------------|--------------------------------------------|
| Delovni tlak                               | Max. 25 bar (on thermowell)                |
| Ohišje                                     | CrNi steel                                 |
| Okvir                                      | CrNi steel                                 |
| Položaj povezave                           | rear                                       |
| Popravek prikaza                           | Trimming pointer                           |
| Povezava                                   | Flush, with collar for thermowell, Ø 18 mm |
| Prednje steklo                             | Flat instrument glass                      |
| Primeren za termometer z dolžino           | SR02 / SR12 / SR22                         |
| Stem                                       | Ø 8 mm, CrNi steel                         |
| Stopnja rasti na območju skale - bar [bar] | 1                                          |
| Vrsta                                      | 52                                         |
| Premer [mm]                                | 100                                        |
| Prikaz območja max. [°C]                   | 120                                        |