

Datum: 30.04.2025



(slika je simbolična)

Cilinder s kratkim hodom del. v dveh smereh bat Ø 50hod 25G 1/4

Kategorija: [Short-stroke cylinder, double-acting, with magnet](#)

Šifra: **115127RIE**

Kratek opis

Short stroke cylinder »ACQ« double-acting, Magnet, Piston Ø 50, Stroke 25, G 1/4, Working pressure 1-10 bar, Temp. -20°C to 70°C

Suitable for installation in limited spaces.

Supplied with magnet.

Short-stroke cylinders in two different versions:

»ACQ« Series, double-acting, Ø 12 to 100

»ASQ« Series, single-acting, Ø 12 to 63

Suitable for filtered, unlubricated or lubricated compressed air.

If lubrication is used, it must be continuous.

Tehnične Specifikacije

Min. temperaturno območje [°C]	-20
Bat	Aluminium
Batnica	Steel, thick-chromed
Batnica IT	M10x1.5
Cushioning	non-cushioned
Ffunkcija	double-acting
Gewinde Kolbenstange	female piston rod
Magnet	with magnet
Ovoj	Aluminium
Povezava	G 1/4
Serijska	ACQ series
Tesnilo	NBR
Min. delovni tlak [bar]	1
Vrsta	3
Max. delovni tlak [bar]	10
Batnica Ø [mm]	20
Stroke [mm]	25
Bat Ø [mm]	50
Max. temperaturno območje [°C]	70