

Datum: 15.12.2025



(slika je simbolična)

Coaxial valve pneumat. actuated, double-acting NC, NBR, Rp 1 1/2

Kategorija: [Coaxial valve, double-acting, NBR](#)

Šifra: **133389RIE**

Kratek opis

Coaxial valve pneumat. actuated, double-acting, NC, nickel-plated brass, Temp. -20°C to 80°C, Control pressure 3-8 bar, Rp 1 1/2

2/2-way coaxial valves, specially designed for automated industrial plant engineering.

A low-price, compact, space-saving and reliable alternative to ball valves with a pneumatic rotary actuator.

These valves have a full bore and - owing to the optimised design - only minimal flow losses.

They are controlled by means of filtered compressed air.

Tehnične Specifikacije

Min. delovna temperatura [°C]	-20
Navoj	Rp 1 1/2
Notranji deli	Nickel-plated brass
Ohišje	Nickel-plated brass
Povezava	NAMUR interface, direct: 2 x G 1/8
Različica	double-acting
Tesnilo	NBR
Vgradni položaj	Any
Vzmet	Stainless steel
Min. vodeni tlak [bar]	3
Max. vodeni tlak [bar]	8
Max. obratovalni tlak [bar]	10
DN	40
Max. delovna temperatura [°C]	80
H [mm]	96.0
L [mm]	180.0