

Datum: 30.04.2025



(slika je simbolična)

## Coaxial valve pneumat. actuated, double-acting, NC, NBR, Rp 3/4

Kategorija: [Coaxial valve, double-acting, NBR](#)

Šifra: **103725RIE**

### Kratek opis

Coaxial valve pneumat. actuated, double-acting, NC, nickel-plated brass, Temp. -20°C to 80°C, Control pressure 3-8 bar, Rp 3/4

2/2-way coaxial valves, specially designed for automated industrial plant engineering.

A low-price, compact, space-saving and reliable alternative to ball valves with a pneumatic rotary actuator.

These valves have a full bore and - owing to the optimised design - only minimal flow losses.

They are controlled by means of filtered compressed air.

### Tehnične Specifikacije

|                               |                                    |
|-------------------------------|------------------------------------|
| Min. delovna temperatura [°C] | -20                                |
| Navoj                         | Rp 3/4                             |
| Notranji deli                 | Nickel-plated brass                |
| Ohišje                        | Nickel-plated brass                |
| Povezava                      | NAMUR interface, direct: 2 x G 1/8 |
| Različica                     | double-acting                      |
| Tesnilo                       | NBR                                |
| Vgradni položaj               | Any                                |
| Vzmet                         | Stainless steel                    |
| Min. vodeni tlak [bar]        | 3                                  |
| Max. vodeni tlak [bar]        | 8                                  |
| Max. obratovalni tlak [bar]   | 10                                 |
| DN                            | 20                                 |
| H [mm]                        | 63.5                               |
| Max. delovna temperatura [°C] | 80                                 |
| L [mm]                        | 135.0                              |