

Datum: 14.12.2025



(slika je simbolična)

## Dvojni nav. priklj. 245, reduciran, R 3/8 Z.N., R 1/4 Z.N.

Kategorija: [Hexagon nipple 245, reducing, male/male, black](#)

Šifra: **133749RIE**

### Kratek opis

Double threaded nipple 245, reducing, R 3/8 ET, R 1/4 ET, black malleable iron fitting, operating temp. -20 °C to 300 °C, ISO 7-1

According to DIN EN 10242 (previously 2950).

Malleable iron cast fittings in black steel, non-galvanized, is the classic fitting series in connection series in piping construction. Our malleable iron cast fittings are characterized by high mechanical strength and standardized fitting technology.

Working minimal temperature = -20 °C, 25 bar.

Working pressure for temperature range from -20 °C to 120 °C: 25 bar.

Working pressure for temperature range from 120 °C to 300 °C: 20-25 bar.

### Tehnične Specifikacije

|                                |                                                     |
|--------------------------------|-----------------------------------------------------|
| Min. temperaturno območje [°C] | -20                                                 |
| Material                       | Black malleable iron<br>B350-10, design<br>symbol A |
| Navoj 1                        | R 3/8                                               |
| Navoj 2                        | R 1/4                                               |
| Površina                       | Black                                               |
| Standardni navoj               | acc. ISO 7-1                                        |
| Max. temperaturno območje [°C] | 300                                                 |