

Datum: 01.05.2025



(slika je simbolična)

Dvoročna varnostna konzola, hitri priklop za cev 4 mm

Kategorija: [Complete pushbutton panel](#)

Šifra: **106711RIE**

Kratek opis

Two-handed safety console, complete, Quick-connect plug hose 4 mm, Operating pressure 2.5 - 8 bar, Temp. -10 °C to 60 °C

This pushbutton panel according to EN574 Type III A is comprised of a dual manual control valve with a housing and manifold. The valve only generates an output signal if two synchronised input signals are received within < 0.4 sec. If one input signal is interrupted, the output signal is interrupted as well. An emergency stop valve with a mushroom pushbutton is included. The housing can be screwed to the wall in any position; the valve manifold can optionally be supplied without the housing and with a DIN bar adapter.

Applications: Two-hand safety valve for start-of-cycle control on a pneumatically operated machine.

Tehnične Specifikacije

Min. temperaturno območje [°C]	-10
Delovanje	Pneumatic
Opis	Complete pushbutton panel with safety valve
Povezava	Push-in fitting for 4 mm pipe
Srednje	Filtered, unlubricated compressed air
Sinhronizacija, max. čas med dvema signaloma [sec.]	0.4
Min. obratovalni tlak [bar]	2.5
Max. obratovalni tlak [bar]	8
Max. temperaturno območje [°C]	60
Pretok pri 6 bar in Δp 1,0 bar [l/min]	85