

Datum: 16.12.2025



(slika je simbolična)

## Filter»FUTURA«Kov. pos.5µm, Vel. 4, G3/4, Pol avto.

Kategorija: [Filter with metal bowl and sight glass](#)

Šifra: **156554RIE**

### Kratek opis

Filter »FUTURA« with metal container and viewing tube, 5 µm, Size 4, G 3/4, 1.5 - 16 bar, Temp. -10 °C to 50 °C, Semi-automatic  
Filters with excellent flow rates in modern design.

### Tehnične Specifikacije

|                                |                                                                    |
|--------------------------------|--------------------------------------------------------------------|
| Min. temperaturno območje [°C] | -10                                                                |
| Element filtra                 | Cellpor (PE)                                                       |
| Merjenje pretoka               | At P <sub>2</sub> = 6 bar and pressure drop Δ <sub>p</sub> = 1 bar |
| Navoj                          | G 3/4                                                              |
| Odtok kondenzata               | Semi-automatic                                                     |
| Ohišje                         | PA66 GF60                                                          |
| Posoda                         | Metal container with viewing tube                                  |
| Priključni navoj               | Material: Die-cast zinc                                            |
| Serijska                       | FUTURA                                                             |
| Srednje                        | Compressed air, neutral gases                                      |
| Tesnilo                        | NBR                                                                |
| Min. vhodni tlak [bar]         | 1.5                                                                |
| Velikost                       | 4                                                                  |
| Rang filtra [µm]               | 5                                                                  |
| Max. vhodni tlak [bar]         | 16                                                                 |
| Max. temperaturno območje [°C] | 50                                                                 |
| C [mm]                         | 58.0                                                               |
| A [mm]                         | 85.0                                                               |
| B [mm]                         | 247.0                                                              |
| Pretok [l/min]                 | 8000                                                               |