

Datum: 15.12.2025



(slika je simbolična)

## Filter nikljana medenina, G 1 1/4, DN 32, šrina mrežice 0.3 mm

Kategorija: [Dirt strainer nickel-plated brass, mesh width 0.3](#)

Šifra: **141006RIE**

### Kratek opis

Dirt strainer, nickel-plated brass, Sieve insert mesh width 0.3 mm, Operating temp. -20°C to 110°C, G 1 1/4, DN 32, PN max. 20 bar  
Suitable for domestic water services, heating and air conditioning plants or compressed air systems. Not suitable for steam.

### Tehnične Specifikacije

|                               |                                               |
|-------------------------------|-----------------------------------------------|
| Min. delovna temperatura [°C] | -20                                           |
| Glava                         | Nickel-plated brass                           |
| Navoj                         | G 1 1/4                                       |
| Ohišje                        | Nickel-plated brass                           |
| Standardni navoj              | G thread acc. to ISO 228-1, tolerance class B |
| Tesnilo                       | NBR O-ring                                    |
| Zaslon                        | Stainless steel                               |
| Velikost mrežice [mm]         | 0.3                                           |
| Max. obratovalni tlak [bar]   | 20                                            |
| DN                            | 32                                            |
| a/f 2 [mm]                    | 36                                            |
| a/f 1 [mm]                    | 47                                            |
| C [mm]                        | 64.0                                          |
| L [mm]                        | 96.0                                          |
| Max. delovna temperatura [°C] | 110                                           |