

Datum: 15.12.2025



## Filter nikljana medenina, G 3/4, DN 20, šrina mrežice 0.5 mm

(slika je simbolična)

Kategorija: [Dirt strainer nickel-plated brass, mesh width 0.5](#)

Šifra: **140996RIE**

### Kratek opis

Dirt strainer, nickel-plated brass, Sieve insert mesh width 0.5 mm, Operating temp. -20 °C to 110 °C, G 3/4, DN 20, PN max. 20 bar

Suitable for domestic water services, heating and air conditioning plants or compressed air systems. Not suitable for steam.

### Tehnične Specifikacije

|                               |                                               |
|-------------------------------|-----------------------------------------------|
| Min. delovna temperatura [°C] | -20                                           |
| Glava                         | Nickel-plated brass                           |
| Navoj                         | G 3/4                                         |
| Ohišje                        | Nickel-plated brass                           |
| Standardni navoj              | G thread acc. to ISO 228-1, tolerance class B |
| Tesnilo                       | NBR O-ring                                    |
| Zaslon                        | Stainless steel                               |
| Velikost mrežice [mm]         | 0.5                                           |
| DN                            | 20                                            |
| Max. obratovalni tlak [bar]   | 20                                            |
| a/f 2 [mm]                    | 27                                            |
| a/f 1 [mm]                    | 31                                            |
| C [mm]                        | 48.0                                          |
| L [mm]                        | 70.0                                          |
| Max. delovna temperatura [°C] | 110                                           |