

Datum: 30.04.2025



(slika je simbolična)

Filter reg.»FUTURA« Kov. Vel.2, G 1/2, 0.5-16 bar Pol avto.Kategorija: [Filter regulator with metal bowl and sight glass](#)Šifra: **139495RIE****Kratek opis**

Filter regulator »FUTURA«, with metal container, Viewing tube, Pressure gauge, 5 µm, Size 2, G 1/2, Control range 0.5-16 bar, Semi
Filter regulators with excellent flow rates in modern design.
The regulator knob can be latched and locked.

Tehnične Specifikacije

Min. temperaturno območje [°C]	-10
Element filtra	Cellpor (PE)
Membrane	NBR
Merjenje pretoka	At $P_1 = 10$ bar, $P_2 = 6.3$ bar and pressure drop $\Delta p = 1$ bar
Navoj	G 1/2
Odtok kondenzata	Semi-automatic
Ohišje	PA66 GF60
Posoda	Metal container with viewing tube
Priključni navoj	Material: Die-cast zinc
Serijska	FUTURA
Srednje	Compressed air, neutral gases
Tesnilo	NBR
Min. krmilno območje [bar]	0.5
Min. vhodni tlak [bar]	1.5
Velikost	2
Rang filtra [µm]	5
Max. krmilno območje [bar]	16
Max. vhodni tlak [bar]	16
Zaslon manometra max. [bar]	25
Max. temperaturno območje [°C]	50
A [mm]	63.0
C [mm]	110.0
B [mm]	261.0
Pretok [l/min]	5200