

Datum: 29.04.2025

**Filter reg. »multifix«5 µmVel.1,G 1/4, 0.5 - 10 bar**

(slika je simbolična)

Kategorija: [Filter regulator with metal bowl and sight glass](#)Šifra: **100493RIE****Kratek opis**

Filter regulator »multifix« with metal container, Viewing tube and press. gauge, 5 µm, Size 1, G 1/4, Input pressure max. 20 bar

Reversible diaphragm pressure regulators, independent of inlet pressure, with self-relieving design, combined with a centrifugal separator.

The pressure setting can be locked by pushing the button down.

**Tehnične Specifikacije**

|                              |                                                                         |
|------------------------------|-------------------------------------------------------------------------|
| Merjenje pretoka             | At $P_1 = 10$ bar, $P_2 = 6,3$ bar and pressure drop $\Delta_p = 1$ bar |
| Navoj                        | G 1/4                                                                   |
| Odtok kondenzata             | Semi-automatic                                                          |
| Ohišje                       | Die-cast zinc                                                           |
| Posoda                       | Metal container with viewing tube                                       |
| Serija                       | multifix                                                                |
| Tesnilo                      | NBR                                                                     |
| Vzmet pokrova motorja        | POM-brass                                                               |
| Min. krmilno območje [bar]   | 0.5                                                                     |
| Velikost                     | 1                                                                       |
| Rang filtra [µm]             | 5                                                                       |
| DN                           | 6                                                                       |
| Max. krmilno območje [bar]   | 10                                                                      |
| Zaslon manometra max. [bar]  | 16                                                                      |
| Max. vhodni tlak [bar]       | 20                                                                      |
| A [mm]                       | 47.8                                                                    |
| Max. sobna temperatura [°C]  | 60                                                                      |
| Max. temperatura medija [°C] | 60                                                                      |
| C [mm]                       | 67.0                                                                    |
| D [mm]                       | 125.5                                                                   |
| B [mm]                       | 192.5                                                                   |
| Pretok [l/min]               | 1600                                                                    |