

Datum: 29.04.2025



(slika je simbolična)

Filter reg. »Stinard«Zašč. kletka5 µmVel.1,G 1/4

Kategorija: [Filter regulator with PC bowl and bowl guard](#)Šifra: **100928RIE**

Kratek opis

Filter regulator »Standard«, PC container, Protective cage, 5 µm, Size 1, G 1/4, Input pressure max. 16 bar, 0.5 - 10 bar Reversible diaphragm pressure regulators, independent of inlet pressure, with selfrelieving design, combined with a centrifugal separator.

Tehnične Specifikacije

Merjenje pretoka	At $P_1 = 8$ bar, $P_2 = 6$ bar and pressure drop $\Delta p = 1$ bar
Navoj	G 1/4
Odtok kondenzata	Semi-automatic
Ohišje	Die-cast zinc, painted silver
Posoda	Polycarbonate container with protective cage
Serijska	Standard
Tesnilo	NBR
Min. krmilno območje [bar]	0.5
Velikost	1
Rang filtra [µm]	5
DN	8
Max. krmilno območje [bar]	10
Max. vhodni tlak [bar]	16
Zaslon manometra max. [bar]	16
A [mm]	54.0
Max. sobna temperatura [°C]	60
Max. temperatura medija [°C]	60
F [mm]	62.0
C [mm]	106.5
D [mm]	129.7
Pretok [l/min]	900