

Datum: 17.12.2025

**Filter regulator »GA«, PC zbiralnik, 5 µm, Velikost 300, G 1/2**

(slika je simbolična)

Kategorija: [Filter regulator with PC bowl, bowl guard](#)Šifra: **178477RIE****Kratek opis**

Filter regulator »GA«, with PC container, Protective cage, Mounting bracket, 5 µm, Size 300, G 1/2, Input pressure max. 10 bar

Reversible diaphragm pressure regulators, independent of inlet pressure, with self-relieving design, combined with a centrifugal separator. The pressure setting can be locked by pushing the button down.

Tehnične Specifikacije

Min. temperaturno območje [°C]	-5
Merjenje pretoka	At $P_1 = 8 \text{ bar}$, $P_2 = 6 \text{ bar}$ and pressure drop $\Delta p = 1 \text{ bar}$
Navoj	G 1/2
Odtok kondenzata	Fully-automatic
Ohišje	Die-cast aluminium
Posoda	Polycarbonate container with protective cage
Serija	GA
Tesnilo	NBR
Vzmet pokrova motorja	POM
Min. krmilno območje [bar]	1.5
Rang filtra [µm]	5
Max. krmilno območje [bar]	9
Max. vhodni tlak [bar]	10
A [mm]	62.5
Max. temperaturno območje [°C]	70
C [mm]	89.0
D [mm]	158.0
B [mm]	247.0
Velikost	300
Pretok [l/min]	2100