

Datum: 15.12.2025

**Filter regulator »multifix«, 5 µm, Velikost 4, G 1, 0.5 - 10 bar**

(slika je simbolična)

Kategorija: [Filter regulator with metal bowl and sight glass](#)Šifra: **133110RIE****Kratek opis**

Filter regulator »multifix« with metal container, Viewing tube and press. gauge, 5 µm, Size 4, G 1, Input pressure max. 20 bar
Reversible diaphragm pressure regulators, independent of inlet pressure, with self-relieving design, combined with a centrifugal separator.
The pressure setting can be locked by pushing the button down.

Tehnične Specifikacije

Merjenje pretoka	At $P_1 = 10$ bar, $P_2 = 6,3$ bar and pressure drop $\Delta p = 1$ bar
Navoj	G 1
Odtok kondenzata	Semi-automatic
Ohišje	Die-cast aluminium
Poraba zraka	Yes
Posoda	Metal container with viewing tube
Serijska	multifix
Tesnilo	NBR
Vzmet pokrova motorja	POM-brass
Min. krmilno območje [bar]	0.5
Max. notranja poraba zraka	1,5 l/min (depending on secondary pressure)
Velikost	4
Rang filtra [µm]	5
Max. krmilno območje [bar]	10
Zaslon manometra max. [bar]	16
Max. vhodni tlak [bar]	20
DN	25
Max. sobna temperatura [°C]	60
Max. temperatura medija [°C]	60
A [mm]	85.0
C [mm]	125.0
D [mm]	189.0
B [mm]	314.0
Pretok [l/min]	12000