

Datum: 29.04.2025



(slika je simbolična)

## **Filter regulator »variobloc« z zaščitno kletko, Velikost 2, G 3/4**

Kategorija: [Filter regulator with PC bowl and bowl guard](#)Šifra: **124796RIE**

### **Kratek opis**

Filter regulator »variobloc«, PC container, Protective cage and pressure gauge, Size 2, G 3/4, Input pressure max. 16 bar

Reversible diaphragm pressure regulators, independent of inlet pressure, with self-relieving design, combined with a centrifugal separator.

The pressure setting can be locked by pushing the knob down.

Approved series in modern industrial design, with the following key benefits:

- Simple handling
- Convenient modular assembly thanks to innovative fasteners
- Excellent flow values

### **Tehnične Specifikacije**

|                              |                                                                       |
|------------------------------|-----------------------------------------------------------------------|
| Membrane                     | NBR                                                                   |
| Merjenje pretoka             | At $P_1 = 10$ bar, $P_2 = 6$ bar and pressure drop $\Delta p = 1$ bar |
| Navoj                        | G 3/4                                                                 |
| Odtok kondenzata             | Manual                                                                |
| Ohišje                       | Die-cast zinc                                                         |
| Posoda                       | Polycarbonate container with protective cage variobloc                |
| Serija                       | NBR                                                                   |
| Tesnilo                      | POM                                                                   |
| Vzmet pokrova motorja        | 0.5                                                                   |
| Min. krmilno območje [bar]   | 2                                                                     |
| Velikost                     | 10                                                                    |
| Max. krmilno območje [bar]   | 10                                                                    |
| Zaslon manometra max. [bar]  | 16                                                                    |
| Max. vhodni tlak [bar]       | 40                                                                    |
| Rang filtra [ $\mu$ m]       | 50                                                                    |
| Max. sobna temperatura [°C]  | 50                                                                    |
| Max. temperatura medija [°C] | 70.0                                                                  |
| A [mm]                       | 98.0                                                                  |
| C [mm]                       | 273.0                                                                 |
| B [mm]                       | 6500                                                                  |
| Pretok [l/min]               |                                                                       |