

Datum: 30.04.2025



(slika je simbolična)

## Filter-regulator Zašč. kletka Vel.1,G 1/4, 0.5 - 16 bar

Kategorija: [Combined service unit, PC bowl and bowl guard](#)Šifra: **101099RIE**

### Kratek opis

Combi-service unit with PC container and Protective cage, Size 1, G 1/4, Input pressure max. 16 bar, Control range 0.5 - 16 bar

A filter, pressure regulator and oil-mist lubricator combined in a single device with an extremely compact design.

The pressure setting can be locked by pushing the knob down.

Oil can be filled under pressure.

### Tehnične Specifikacije

|                              |                                                                      |
|------------------------------|----------------------------------------------------------------------|
| Merjenje pretoka             | At $P_1 = 8$ bar, $P_2 = 6$ bar and pressure drop $\Delta p = 1$ bar |
| Navoj                        | G 1/4                                                                |
| Odtok kondenzata             | Manual drain valve                                                   |
| Ohišje                       | Die-cast zinc                                                        |
| Posoda                       | Polycarbonate container with protective cage                         |
| Tesnilo                      | NBR                                                                  |
| Vidna kupola                 | PA                                                                   |
| Vzmet pokrova motorja        | PA                                                                   |
| Min. krmilno območje [bar]   | 0.5                                                                  |
| Velikost                     | 1                                                                    |
| Max. krmilno območje [bar]   | 16                                                                   |
| Max. vhodni tlak [bar]       | 16                                                                   |
| Rang filtra [ $\mu$ m]       | 40                                                                   |
| Max. sobna temperatura [°C]  | 50                                                                   |
| Max. temperatura medija [°C] | 50                                                                   |
| A [mm]                       | 67.0                                                                 |
| C [mm]                       | 68.5                                                                 |
| B [mm]                       | 217.0                                                                |
| Pretok [l/min]               | 1000                                                                 |