

Datum: 15.12.2025



(slika je simbolična)

Filter »variobloc«PC zbir.Zašč. kletkaVel. 2G 1

Kategorija: [Filter with polycarbonate bowl and bowl guard](#)

Šifra: **124773RIE**

Kratek opis

Filter »variobloc«, Polycarbonate container and protective cage, Size 2, G 1, Input pressure max. 16 bar, Manual bleeder valve

Centrifugal separators with a sintered filter element. Filtration takes place in a 2-stage process comprising cyclone separation (condensate) and a PE filter element (particles).

Approved series in modern industrial design, with the following key benefits:

- Simple handling
- Convenient modular assembly thanks to innovative fasteners
- Excellent flow values

Tehnične Specifikacije

Merjenje pretoka	At $P_1 = 6$ bar and pressure drop $\Delta p = 1$ bar
Navoj	G 1
Odtok kondenzata	Manual
Ohišje	Die-cast zinc
Posoda	Polycarbonate container with protective cage variobloc
Serijska	NBR
Tesnilo	2
Velikost	16
Max. vhodni tlak [bar]	26.0
C [mm]	40
Rang filtra [μ m]	50
Max. sobna temperatura [°C]	50
Max. temperatura medija [°C]	124.0
A [mm]	202.0
B [mm]	3500
Pretok [l/min]	