

Datum: 29.04.2025



(slika je simbolična)

Filter »variobloc« s kovinsko posodo, Velikost 2, G 3/4

Kategorija: [Filter with metal bowl incl. sight glass](#)

Šifra: **125318RIE**

Kratek opis

Filter »variobloc« with metal container incl. viewing tube, Size 2, G 3/4, Input pressure max. 20 bar, Manual bleeder valve

Centrifugal separators with a sintered filter element. Filtration takes place in a 2-stage process comprising cyclone separation (condensate) and a PE filter element (particles).

Approved series in modern industrial design, with the following key benefits:

- Simple handling
- Convenient modular assembly thanks to innovative fasteners
- Excellent flow values

Tehnične Specifikacije

Merjenje pretoka	At $P_1 = 6$ bar and pressure drop $\Delta_p = 1$ bar
Navoj	G 3/4
Odtok kondenzata	Manual
Ohišje	Die-cast zinc
Posoda	Metal container with viewing tube
Serijska	variobloc
Tesnilo	NBR
Velikost	2
Max. vhodni tlak [bar]	20
C [mm]	26.0
Rang filtra [μ m]	40
A [mm]	70.0
Max. sobna temperatura [°C]	80
Max. temperatura medija [°C]	80
B [mm]	202.0
Pretok [l/min]	3500