

Datum: 29.04.2025



(slika je simbolična)

Filter »variobloc« z PC zbiralnik, Velikost 1, G 3/8

Kategorija: [Filter with polycarbonate bowl](#)

Šifra: **100679RIE**

Kratek opis

Filter »variobloc«, PC container, Size 1, G 3/8, Input pressure max. 16 bar, Med. / ambient temp. max. 50 °C, Manual bleeder valve

Centrifugal separators with a sintered filter element. Filtration takes place in a 2-stage process comprising cyclone separation (condensate) and a PE filter element (particles).

Approved series in modern industrial design, with the following key benefits:

- Simple handling
- Convenient modular assembly thanks to innovative fasteners
- Excellent flow values

Tehnične Specifikacije

Merjenje pretoka	At $P_1 = 6$ bar and pressure drop $\Delta p = 1$ bar
Navoj	G 3/8
Odtok kondenzata	Manual
Ohišje	Die-cast zinc
Posoda	Polycarbonate container
Serija	variobloc
Tesnilo	NBR
Velikost	1
Max. vhodni tlak [bar]	16
C [mm]	22.0
Rang filtra [μ m]	40
A [mm]	48.0
Max. sobna temperatura [°C]	50
Max. temperatura medija [°C]	50
B [mm]	155.0
Pretok [l/min]	2000