

Datum: 29.04.2025



(slika je simbolična)

## Filter z aktivnim ogljem »multifix«Kov. pos.Vel. 4G 1

Kategorija: [Activated carbon filter with metal bowl](#)

Šifra: **133152RIE**

### Kratek opis

Active charcoal filter »multifix« with metal container, 0.005 mg/m<sup>3</sup>, Size 4, G 1, Input pressure max. 20 bar, Temp. max. 60 °C

For filtering odours out of compressed air.

The activated carbon absorbs the oil vapour molecules contained in the compressed air.

A separate filter route prevents activated carbon particles from entering the air flow.

### Tehnične Specifikacije

|                                              |                                                                      |
|----------------------------------------------|----------------------------------------------------------------------|
| Element filtra                               | Activated carbon-POM                                                 |
| Merjenje pretoka                             | At P <sub>1</sub> = 6 bar and pressure drop Δ <sub>p</sub> = 0.2 bar |
| Navoj                                        | G 1                                                                  |
| Ohišje                                       | Die-cast aluminium                                                   |
| Posoda                                       | Metal container                                                      |
| Serijska                                     | multifix                                                             |
| Tesnilo                                      | NBR                                                                  |
| Vsebnost olja v ostanku [mg/m <sup>3</sup> ] | 0.005                                                                |
| Velikost                                     | 4                                                                    |
| Max. vhodni tlak [bar]                       | 20                                                                   |
| DN                                           | 25                                                                   |
| C [mm]                                       | 58.0                                                                 |
| Max. sobna temperatura [°C]                  | 60                                                                   |
| Max. temperatura medija [°C]                 | 60                                                                   |
| A [mm]                                       | 85.0                                                                 |
| D [mm]                                       | 182.0                                                                |
| B [mm]                                       | 240.0                                                                |
| Pretok [l/min]                               | 3000                                                                 |