

Datum: 29.04.2025



(slika je simbolična)

## Filter z aktivnim ogljem »variobloc« Kov. pos.Vel. 2G 1

Kategorija: [Activated carbon filter with metal bowl](#)

Šifra: **125334RIE**

### Kratek opis

Active charcoal filter »variobloc« with metal container incl. viewing tube, 0.003 mg/m<sup>3</sup>, Size 2, G 1, Input pressure max. 20 bar

Activated carbon filters are used to absorb oil vapour from the compressed air. The incoming compressed air should be dry and free of impurities (upstream connection of a micro-filter is recommended).

### Tehnične Specifikacije

|                                              |                                                          |
|----------------------------------------------|----------------------------------------------------------|
| Kakovost zraka po ISO                        | Class 1 dirt, class 1 oil                                |
| 8573.1                                       | At P <sub>1</sub> = 7 bar and pressure drop Δp = 0,2 bar |
| Merjenje pretoka                             | G 1                                                      |
| Navoj                                        | Metal container with viewing tube                        |
| Posoda                                       | variobloc                                                |
| Serijska                                     |                                                          |
| Vsebnost olja v ostanku [mg/m <sup>3</sup> ] | 0.003                                                    |
| Velikost                                     | 2                                                        |
| Max. vhodni tlak [bar]                       | 20                                                       |
| C [mm]                                       | 26.0                                                     |
| Max. temperatura medija [°C]                 | 50                                                       |
| Max. sobna temperatura [°C]                  | 80                                                       |
| A [mm]                                       | 124.0                                                    |
| B [mm]                                       | 193.0                                                    |
| Pretok [l/min]                               | 1300                                                     |