

Datum: 17.12.2025



(slika je simbolična)

## Glicerinski man.cent. priklop zadaj G 1/4, -1/0 bar, Ø 63

Kategorija: [Glycerine pressure gauge, conn. rear, central](#)

Šifra: **102143RIE**

### Kratek opis

Glycerine pressure gauge, CrNi steel housing, Connection, rear, centric, G 1/4, Goods class 1.6, Measurement range -1/0 bar, Ø 63

Glycerine-filled bourdon-tube pressure gauge.

For measurements in areas with high, dynamic pressure loads and vibration levels.

Suitable for gaseous or liquid media which do not corrode copper alloy, do not have high viscosity and do not crystallise.

### Tehnične Specifikacije

|                                            |                                                      |
|--------------------------------------------|------------------------------------------------------|
| Min. sobna temperatura [°C]                | -20                                                  |
| Min. temperatura medija [°C]               | -20                                                  |
| Merilno območje min. bar                   | -1                                                   |
| Material Prozessanschluss                  | Copper alloy                                         |
| Merilni element                            | Copper alloy                                         |
| Ohišje                                     | CrNi steel, with bare metal surface                  |
| Položaj povezave                           | rear, central                                        |
| Povezava                                   | G 1/4                                                |
| Prednje steklo                             | Transparent plastic                                  |
| Premikanje                                 | Copper alloy                                         |
| Spodnja/Zgornja meja območja               | Vacuum                                               |
| Stisnjen okvir                             | CrNi steel, with glossy metal surface (3-hole bezel) |
| Stopnja rasti na območju skale - bar [bar] | 0.05                                                 |
| Razred točnosti                            | 1.6                                                  |
| Max. sobna temperatura [°C]                | 60                                                   |
| Max. temperatura medija [°C]               | 60                                                   |
| Premier [mm]                               | 63                                                   |
| Vrsta                                      | 213.53                                               |