

Datum: 01.05.2025



(slika je simbolična)

Glicerinski man.cent. priklop zadaj G 1/4, 0-400 bar, Ø 63

Kategorija: [Glycerine pressure gauge, conn. rear, central](#)

Šifra: **102107RIE**

Kratek opis

Glycerine pressure gauge, plastic housing, Connection, rear, centric, G 1/4, Goods class 2.5, Measurement range 0-400 bar, Ø 63

Glycerine-filled bourdon-tube pressure gauge.

For measurements in areas with high, dynamic pressure loads and vibration levels.

Suitable for gaseous or liquid media which do not corrode copper alloy, do not have high viscosity and do not crystallise.

Tehnične Specifikacije

Min. sobna temperatura [°C]	-20
Min. temperatura medija [°C]	-20
Material Prozessanschluss	Copper alloy
Merilni element	Copper alloy
Ohišje	Plastic, black (with panel-mounting bezel)
Položaj povezave	rear, central
Povezava	G 1/4
Prednje steklo	PMMA, welded to housing
Premikanje	Copper alloy
Spodnja/Zgornja meja območja	Positive pressure
Razred točnosti	2.5
Merilno območje max. psi	5.800
Stopnja rasti na območju skale - bar [bar]	20
Max. sobna temperatura [°C]	60
Max. temperatura medija [°C]	60
Premier [mm]	63
Vrsta	113.13
Merilno območje max. bar	400