

Datum: 16.12.2025



(slika je simbolična)

## Glicerinski man.trikoten sprednji obročG 1/4, 0-400 bar

Kategorija: [Glycerine pressure gauges with clamp fixing](#)

Šifra: **102291RIE**

### Kratek opis

Glycerine pressure gauge, bracket fastening, triangle front ring, Connection, rear, centric, G 1/4, Meas. range 0 - 400 bar, Ø 63

Bourdon-tube pressure gauge in standard design, with clamp fixing.

For measurements in areas with high, dynamic pressure loads and vibration levels.

Suitable for gaseous or liquid media which do not corrode copper alloy,  
do not have high viscosity and do not crystallise.

### Tehnične Specifikacije

|                                            |                   |
|--------------------------------------------|-------------------|
| Min. sobna temperatura [°C]                | -20               |
| Min. temperatura medija [°C]               | -20               |
| Material Prozessanschluss                  | Copper alloy      |
| Merilni element                            | Copper alloy      |
| Ohišje                                     | Hot-pressed brass |
| Položaj povezave                           | rear, central     |
| Povezava                                   | G 1/4             |
| Prednje steklo                             | Plexiglass        |
| Premikanje                                 | Copper alloy      |
| Spodnja/Zgornja meja območja               | Positive pressure |
| Razred točnosti                            | 1.6               |
| Stopnja rasti na območju skale - bar [bar] | 20                |
| Max. sobna temperatura [°C]                | 60                |
| Max. temperatura medija [°C]               | 60                |
| Premier [mm]                               | 63                |
| Vrsta                                      | 213.40            |
| Merilno območje max. bar                   | 400               |