

Datum: 30.04.2025



Glicerinski manometer, CrNi jeklo, G 1/2, 0 - 400 bar, Ø 100

(slika je simbolična)

Kategorija: [Glycerine pressure gauges, CrNi steel - 233.30](#)

Šifra: **102404RIE**

Kratek opis

Glycerine pressure gauge, CrNi steel safety design, Connection radial bottom, G 1/2, Measurement range 0 - 400 bar, Ø 100

Glycerine-filled bourdon-tube pressure gauge, CrNi steel type, with solid baffle wall and blow-out (safety housing). Suitable for gaseous or liquid, corrosive and crystallising media which do not have high viscosity, also in corrosive atmosphere.

Tehnične Specifikacije

Min. sobna temperatura [°C]	-20
Min. temperatura medija [°C]	-20
Material	CrNi steel
Material Prozessanschluss	CrNi steel
Položaj povezave	radial on bottom
Povezava	G 1/2
Prednje steklo	Laminated safety glass
Spodnja/Zgornja meja območja	Positive pressure
Razred točnosti	1.0
Stopnja rasti na območju skale - bar [bar]	10
Max. sobna temperatura [°C]	60
Max. temperatura medija [°C]	100
Premer [mm]	100
Vrsta	233.30
Merilno območje max. bar	400