

Datum: 29.04.2025



(slika je simbolična)

Glicerinski manometer, CrNi jeklo, G 1/4, 0 - 4 bar, Ø 63

Kategorija: [Glycerine pressure gauges, CrNi steel - 233.30](#)

Šifra: **102377RIE**

Kratek opis

Glycerine pressure gauge, CrNi steel safety design,
Connection radial bottom, G 1/4, Measurement range 0 - 4
bar, Ø 63

Glycerine-filled bourdon-tube pressure gauge, CrNi steel
type, with solid baffle wall and blow-out (safety housing).
Suitable for gaseous or liquid, corrosive and crystallising
media which do not have high viscosity, also in corrosive
atmosphere.

Tehnične Specifikacije

Min. sobna temperatura [°C]	-20
Min. temperatura medija [°C]	-20
Material	CrNi steel
Material Prozessanschluss	CrNi steel
Položaj povezave	radial on bottom
Povezava	G 1/4
Prednje steklo	Polycarbonate
Spodnja/Zgornja meja območja	Positive pressure
Stopnja rasti na območju skale - bar [bar]	0.2
Razred točnosti	1.6
Merilno območje max. bar	4
Max. sobna temperatura [°C]	60
Premer [mm]	63
Max. temperatura medija [°C]	100
Vrsta	233.30