

Datum: 18.12.2025



(slika je simbolična)

Glicerinski manometer »pressure line« G 1/4, 0-400bar/6000 psi

Kategorija: [Glycerine pressure gauge, connection on rear](#)

Šifra: **116336RIE**

Kratek opis

Glycerine press. gauge »pressure line« Connection, rear, centric, G 1/4, Goods class 1.6, Measurement range 0-400bar/6000 psi, Ø63

Low-priced series of high-quality, glycerine-filled pressure gauges with stainless steel housing for all applications involving measurements in areas with high dynamic pressure loads and vibration levels.

Suitable for gaseous or liquid media which do not corrode copper alloy, do not have high viscosity and do not crystallise.

Tehnične Specifikacije

Min. sobna temperatura [°C]	-20
Min. temperatura medija [°C]	-20
Material Prozessanschluss	Copper alloy
Merilni element	Brass
Ohišje	Stainless steel
Položaj povezave	rear, central
Povezava	G 1/4
Prednje steklo	Glass
Premikanje	Brass
	Bourdon-tube
Različica	pressure gauge with glycerine filling
	1.6
Razred točnosti	10
Stopnja rasti na območju skale - bar [bar]	60
Max. sobna temperatura [°C]	60
Max. temperatura medija [°C]	63
Premier [mm]	400
Merilno območje max. bar	