

Datum: 29.04.2025



(slika je simbolična)

Hidravlična spojka zakl. na obeh str., Med.G 1/4 N.N.I.D. 6.3

Kategorija: [Self-sealing plugs, bright brass, female](#)

Šifra: **107699RIE**

Kratek opis

Closing nipple locking on both sides, Bright brass, G 1/4 IT, I.D. 6.3, Operating pressure max. 200 bar, Temp. -20 °C to 100 °C

Tehnične Specifikacije

Min. sobna temperatura [°C]	-20
Min. temperatura medija [°C]	-20
Delovni tlak	Referred to medium temp. of 50 °C, static working pressure
Krogla	Stainless steel
Merjenje pretoka	at 6 bar and $\Delta p = 0.5$ bar
Ohišje	Brass with a bare metal surface
Povezava	G 1/4 IT
Pritrdilni obroč	Stainless steel
Rokav	Brass with a bare metal surface
Tesnilo	NBR
Ventil	Brass with a bare metal surface
Vzmet	Stainless steel
DN	6.3
a/f [mm]	19
Dolžina [mm]	35.3
Max. sobna temperatura [°C]	100
Max. temperatura medija [°C]	100
Max. obratovalni tlak [bar]	200
Volumski pretok (zrak) [l/min]	840