

Datum: 29.04.2025



(slika je simbolična)

## Hidravlična spojka zakl. na obeh str.1.4305G 1/8 N.N.I.D. 4.3

Kategorija: [Self-sealing plugs, stainless steel 1.4305, female](#)  
Šifra: **107708RIE**

### Kratek opis

Closing nipple locking on both sides, Stainless steel 1.4305,  
G 1/8 IT, I.D. 4.3, Operating pressure max. 250 bar

### Tehnične Specifikacije

|                                |                                                            |
|--------------------------------|------------------------------------------------------------|
| Min. sobna temperatura [°C]    | -15                                                        |
| Min. temperatura medija [°C]   | -15                                                        |
| Delovni tlak                   | Referred to medium temp. of 50 °C, static working pressure |
| Krogla                         | Stainless steel 1.4401                                     |
| Merjenje pretoka               | at 6 bar and $\Delta p = 0.5$ bar                          |
| Ohišje                         | Stainless steel 1.4305                                     |
| Povezava                       | G 1/8 IT                                                   |
| Rokav                          | Stainless steel 1.4305                                     |
| Tesnilo                        | FKM                                                        |
| Ventil                         | Stainless steel 1.4305                                     |
| Vzmet                          | Stainless steel 1.4310                                     |
| DN                             | 4.3                                                        |
| a/f [mm]                       | 14                                                         |
| Dolžina [mm]                   | 29.5                                                       |
| Max. sobna temperatura [°C]    | 200                                                        |
| Max. temperatura medija [°C]   | 200                                                        |
| Max. obratovalni tlak [bar]    | 250                                                        |
| Volumski pretok (zrak) [l/min] | 440                                                        |