

Datum: 29.04.2025



(slika je simbolična)

## Hitre spojke I.D. 10, Težka obilka, Fi cevi I.D. 13

Kategorija: [Quick disconnect coupling DN 10, with hose stem](#)

Šifra: **107470RIE**

### Kratek opis

Quick-connect coupling I.D. 10, galvanised steel / brass, Robust design, Sleeve I.D. 13, Operating pressure max. 16 bar

One-hand quick disconnect couplings, one side sealing, that combine optimal flow rates (approx. 4 times as high as the popular standard coupling DN 7.2) with minimal coupling forces.

Suitable for all applications with an above-average air requirement and characterised by extreme conditions!

### Tehnične Specifikacije

|                                |                                                                        |
|--------------------------------|------------------------------------------------------------------------|
| Min. temperaturno območje [°C] | -20                                                                    |
| Material                       | Nickel-plated steel, nickel-plated brass at 6 bar and $\Delta_p = 0.5$ |
| Merjenje pretoka               | bar                                                                    |
| Povezava                       | I.D. 13                                                                |
| Tesnilo                        | NBR                                                                    |
| DN                             | 10                                                                     |
| Max. obratovalni tlak [bar]    | 16                                                                     |
| a/f [mm]                       | 24                                                                     |
| Dolžina [mm]                   | 75.8                                                                   |
| Max. temperaturno območje [°C] | 100                                                                    |
| Pretok                         | 3900 l/min (air)                                                       |