

Datum: 15.12.2025



(slika je simbolična)

Hitre spojke I.D. 2.7, Nerjavno jeklo 1.4305, cev I.D. 4

Kategorija: [Quick disc. coupling DN2.7, 1.4305, with hose stem](#)

Šifra: **156209RIE**

Kratek opis

Quick-connect coupling I.D. 2.7, Stainless steel 1.4305, Sleeve I.D. 4, Operating pressure 0 - 35 bar, Temp. -20 °C to 200 °C

"

One-hand quick disconnect couplings, one side sealing, extremely compact with a large bore and only a small pressure drop.

To prevent injuries or a "whiplash" effect, we recommend that the plug-in nipple is held with one hand during uncoupling.

Areas of application: Pneumatic system, machine and plant engineering, measurement, monitoring and control systems, manufacturing industry, medical technology, chemical / pharmaceutical industry, automotive, food technology, offshore.

"

Tehnične Specifikacije

Min. sobna temperatura [°C]	-20
Min. temperatura medija [°C]	-20
Delovni tlak	0 to 35 bar, maximum static working pressure (non-pulsating)
Krogla	Stainless steel 1.4034
Merjenje pretoka	at 6 bar and $\Delta p = 1$ bar
Ohišje	Stainless steel 1.4305
Povezava	I.D. 4
Pritrdilni obroč	Stainless steel 1.4310
Rokav	Stainless steel 1.4305
Telo ventila	Stainless steel 1.4305
Tesnilo	FPM
Vzmet	Stainless steel 1.4310
DN	2.7
Dolžina [mm]	34.0
Pretok	120 l/min (air)
Max. sobna temperatura [°C]	200
Max. temperatura medija [°C]	200