

Datum: 29.04.2025



(slika je simbolična)

Hitre spojke I.D. 5, Nerjavno jeklo 1.4305, G 1/8 zunanji navoj

Kategorija: [Quick disconnect coupling DN 5, 1.4305, male](#)

Šifra: **107192RIE**

Kratek opis

Quick-connect coupling I.D. 5, Stainless steel 1.4305, G 1/8 ET, Operating pressure 0 - 35 bar, Temp. -15 °C to 200 °C

One-hand quick disconnect couplings, one side sealing, made of stainless steel 1.4305, compact with a large bore. To prevent injuries or a "whiplash" effect, we recommend that the plug-in nipple is held with one hand during uncoupling.

Areas of application: Pneumatic system, measurement, monitoring and control systems, manufacturing industry, medical technology, chemical / pharmaceutical industry, automotive, food technology, offshore.

Tehnične Specifikacije

Min. sobna temperatura [°C]	-15
Min. temperatura medija [°C]	-15
Delovni tlak	0 to 35 bar, maximum static working pressure (non-pulsating)
Krogla	Stainless steel
Merjenje pretoka	at 6 bar and $\Delta p = 0.5$ bar
Ohišje	Stainless steel 1.4305
Povezava	G 1/8 ET
Pritrdilni obroč	Stainless steel
Rokav	Stainless steel 1.4305
Telo ventila	Stainless steel 1.4305
Tesnilo	FKM
Vzmet	Stainless steel
DN	5
a/f [mm]	14
Dolžina [mm]	36.0
Max. sobna temperatura [°C]	200
Max. temperatura medija [°C]	200
Pretok	560 l/min (air)