

Datum: 15.12.2025



(slika je simbolična)

## Hitre spojke I.D. 7.2 zakl. na obeh str.G 1/2 N.N.

Kategorija: [Quick disconnect coupl. DN7.2, bright brass female](#)Šifra: **107511RIE**

### Kratek opis

Quick-connect coupling I.D. 7.2, locking on both sides, Bright brass, G 1/2 IT, Operating pressure 0-35 bar, Temp. -20°C to 100°C

Couplings, stems and plugs are fitted with a valve.

Connection: Both valves open and the medium is allowed to pass.

Disconnection: Both valves close and the medium is prevented from escaping.

Areas of application: Pneumatic system, machine and plant engineering, Measurement, monitoring and control systems, Manufacturing industry, medical technology, chemical / pharmaceutical industry, automotive, food technology, aerospace.

### Tehnične Specifikacije

|                              |                                                              |
|------------------------------|--------------------------------------------------------------|
| Min. sobna temperatura [°C]  | -20                                                          |
| Min. temperatura medija [°C] | -20                                                          |
| Delovni tlak                 | 0 to 35 bar, maximum static working pressure (non-pulsating) |
| Krogla                       | Stainless steel                                              |
| Merjenje pretoka             | at 6 bar and $\Delta p = 0.5$ bar                            |
| Ohišje                       | Brass with a bare metal surface                              |
| Povezava                     | G 1/2 IT                                                     |
| Pritrdilni obroč             | Stainless steel                                              |
| Rokav                        | Brass with a bare metal surface                              |
| Telo ventila                 | Brass with a bare metal surface                              |
| Tesnilo                      | NBR                                                          |
| Vzmet                        | Stainless steel                                              |
| DN                           | 7.2                                                          |
| a/f [mm]                     | 24                                                           |
| Dolžina [mm]                 | 42.5                                                         |
| Max. sobna temperatura [°C]  | 100                                                          |
| Max. temperatura medija [°C] | 100                                                          |
| Pretok                       | 700 l/min (air)                                              |