

Datum: 15.12.2025



(slika je simbolična)

Hitre spojke I.D. 7.8, , toga, cev 10x8

Kategorija: [Quick disconnect coupling DN 7.8, hose connector](#)
Šifra: **141527RIE**

Kratek opis

Quick-connect coupling I.D. 7.8, Steel, Rigid, Hose connection 10x8, Operating pressure 0 - 35 bar, Temp. -20 °C to 100 °C

"
Single-sided blocking, high quality and robust quick connect coupling for high flow values.

To prevent injuries or a ""whiplash"" effect, we recommend that the plug-in nipple is held with one hand during uncoupling.

These quick disconnect couplings are not suitable for direct attachment to pulsating tools.

We recommend using our vibration dampers, according to ISO 6150 § 7.1.

Areas of application: Pneumatic system, machine and plant engineering, measurement, monitoring and control systems, manufacturing industry, medical technology, chemical / pharmaceutical industry, workshops, automotive, mining.

"

Tehnične Specifikacije

Min. sobna temperatura [°C]	-20
Min. temperatura medija [°C]	-20
Delovni tlak	0 - 35 bar
Krogla	Stainless steel
Merjenje pretoka	at 6 bar and $\Delta p = 0.5$ bar
Navojni kos	Galvanised steel
Ohišje	Galvanised steel
Povezava	Hose connection 10x8
Različica	Rigid
Rokav	Galvanised steel
Tesnilo	NBR
Ventil	Die-cast zinc (zamac)
Vzmet	Stainless steel
DN	7.8
a/f [mm]	19
Max. sobna temperatura [°C]	100
Max. temperatura medija [°C]	100
Dolžina [mm]	160.0
Pretok	2000 l/min (air)